

DECLARATION OF PERFORMANCE

No. 13 / 26-1

1. Unique identification code of the product-type:

DRVOLIT AKUSTIK DA A2 (1,5 mm - NATURAL & WHITE)

2. Intended use/es:

Thermal insulation products for buildings

3. Manufacturer:

FRAGMAT H d.o.o., Donja Pačetina 1A, HR-49223 Sveti Križ Začretje

5. System/s of AVCP:

System 1

- 6.a Harmonised standard:

EN 13168:2012+A1:2015

Notified body/ies:

0615 – Bureau Veritas Certification

7. Declared performance/s:

Essential characteristics	Performance	Harmonized technical specification
Thermal resistance	Thermal resistance R_D 0,25 m ² ·K/W	
	4.2.1 Thermal conductivity λ_D 0,096 W/(m·K)	
	4.2.3 Thickness d_N 25	
Reaction to fire	4.2.8 Reaction to fire A2-s1, d0	

Durability of thermal resistance against heat, weathering, ageing/degradation	4.2.1	Thermal resistance	R_D	0,25 $m^2 \cdot K/W$	EN 13168:2012+A1:2015
		Thermal conductivity	λ_D	0,096 $W/(m \cdot K)^b$	
	4.2.9	Durability characteristics		*NPD	
Durability of reaction to fire against heat, weathering, ageing/degradation	4.2.9	Durability characteristics ^a		*NPD	
Compressive strength	4.3.3	Compressive stress or compressive strength		CS(10)300	
	4.3.5	Point load		*NPD	
Tensile/Flexural strength	4.2.7	Tensile strength perpendicular to faces		*NPD	
	4.3.7	Bending strength	BSi	*NPD	
Water vapour permeability	4.3.8	Water vapour transmission		*NPD	
Water permeability	4.3.9	Short term water absorption		*NPD	
Durability of compressive strength against ageing/degradation	4.3.10	Compressive creep		*NPD	
Acoustic absorption indeks	4.3.11	Sound absorption		*table below	
Release of dangerous substances to the indoor environment	4.3.12	Release of dangerous substances		*NPD	
Continuous glowing combustion	4.3.14	Continuous glowing combustion		*NPD	

*NPD - No Performance Determined

- * a - No change in reaction to fire properties for WW products.
The fire performance of WW does not deteriorate with time. The Euroclass classification of the product is related to the organic content, which cannot increase with time.
- * b - Thermal conductivity of WW products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gases than atmospheric air.

Sound absorption coefficient – α_w (EN ISO 11654):

Directly on the substrate	0,30 [D]
With 30 mm spacing from the substrate, without filling	0,50 [C]

*Ceiling installation (other applications in technical documentation)

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dragutin Haldek, director

At Sveti Križ Začretje, on 8.1.2026.

[signature]



 **FRAGMAT**
FRAGMAT H d.o.o., Donja Pačetina 1a,
49223 Sveti Križ Začretje 2

