

DECLARATION OF PERFORMANCE

No. 4 / 26-1

1. Unique identification code of the product-type:

DRVOPOR DP3

2. Intended use/es:

Thermal insulation products for buildings

3. Manufacturer:

FRAGMAT H d.o.o., Donja Pačetina 1A, HR-49223 Sveti Križ Začretje

5. System/s of AVCP:

System 3

- 6.a Harmonised standard:

EN 13168:2012+A1:2015

Notified body/ies:

2477 – INSTITUT IGH d.d., Janka Rakuše 1, HR-10000 Zagreb

7. Declared performance/s:

Essential characteristics	Performance	Harmonized technical specification
Thermal resistance	4.2.1 Thermal resistance R_D *table below Thermal conductivity λ_D EPS: 0,039 W/(m·K) WW: 0,077 W/(m·K)	
	4.2.3 Thickness d_N *table below	
Reaction to fire	4.2.8 Reaction to fire E	
Durability of thermal resistance against heat, weathering, ageing/degradation	4.2.1 Thermal resistance R_D *table below Thermal conductivity λ_D EPS: 0,039 W/(m·K) WW: 0,077 W/(m·K) ^b	

	4.2.9	Durability characteristics	*NPD		EN 13168:2012+A1:2015
Durability of reaction to fire against heat, weathering, ageing/degradation	4.2.9	Durability characteristics ^a	*NPD		
Compressive strength	4.3.3	Compressive stress or compressive strength	CS(10)50		
	4.3.5	Point load	*NPD		
Tensile/Flexural strength	4.2.7	Tensile strength perpendicular to faces	TR40		
	4.3.7	Bending strength	BSi	*table below	
Water vapour permeability	4.3.8	Water vapour transmission	MU _{EPS} 20 - 40 MU _{WW} 5		
Water permeability	4.3.9	Short term water absorption	WS3		
Durability of compressive strength against ageing/degradation	4.3.10	Compressive creep	*NPD		
Acoustic absorption indeks	4.3.11	Sound absorption	*NPD		
Release of dangerous substances to the indoor environment	4.3.12	Release of dangerous substances	*NPD		
Continuous glowing combustion	4.3.14	Continuous glowing combustion	*NPD		
*NPD - No Performance Determined					
* a - No change in reaction to fire properties for WW products. The fire performance of WW does not deteriorate with time. The Euroclass classification of the product is related to the organic content, which cannot increase with time.					
* b - Thermal conductivity of WW products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gases than atmospheric air.					

Thickness - d _N	mm	25	35	50	75
Thermal resistance- R _D	m ² ·K/W	0,50	0,75	1,15	1,75
Bending strength - BSi	kPa	≥ 1000	≥ 700	≥ 500	≥ 400

Thickness - d _N	mm	100	125	150	175
Thermal resistance- R _D	m ² ·K/W	2,40	3,05	3,70	4,35
Bending strength - BSi	kPa	≥ 300	≥ 200	≥ 150	≥ 100

Thickness - d_N	mm	200
Thermal resistance- R_D	$m^2 \cdot K/W$	5,00
Bending strength - BSi	kPa	≥ 75


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dragutin Haldek, director

At Sveti Križ Začretje, on 8.1.2026.

[signature]



 **FRAGMAT**
FRAGMAT H d.o.o., Donja Pačetina 1a,
49223 Sveti Križ Začretje 2